

NEW RELEASE FROM **FALKEN** FK510 RUN FLAT


RUN-FLAT TYRE TECHNOLOGY

Runflat Tyres have reinforced sidewalls that reduce deformation if the tyre sustains damage or a puncture; they can thus continue to be driven for at least a further 80 km at a maximum speed of 80 km/h.

Falken Runflat Tyres combine this 'limp-home' mode with top performance in all areas. Incidentally, manufacturers specify that **Runflat Tyres** must be used with a tyre pressure monitoring system because the tyres are so effective that drivers may not actually notice their tyre has a puncture.



NEO-T01 **NEO-T01 - Next Generation Tyre Manufacturing System, which offers ultra-high precision to create next generation tyres.**



< BEAD CARCASS WRAPPING

The bead carcass is wrapped in the shape of the finished tyre.



< BREAKER TREAD WRAPPING

The automated system wraps the breaker tread accurate to 1/100mm.



< RAW COVER

Since inflation is unnecessary, the shape is almost the same as the finished tyre.



< CURING

The rubber is vulcanised and cured to adhere to the metal core with high precision.

RIM INCH	PRODUCT CODE	SIZE	TREAD PATTERN	NOTES	LOAD / SPEED
PASSENGER					
18"	330721	225/45RF18	FK510	Run-Flat	95Y
	330720	275/40RF18	FK510	Run-Flat	103Y
	330719	245/45RF18	FK510	Run-Flat	100Y
	330722	255/40RF18	FK510	Run-Flat	99Y
	330728	245/50RF18	FK510	Run-Flat	104Y
19"	330725	225/40RF19	FK510	Run-Flat	93Y
	330723	245/40RF19	FK510	Run-Flat	98Y
	330726	255/35RF19	FK510	Run-Flat	96Y
	330724	275/35RF19	FK510	Run-Flat	100Y

FALKEN
ON THE PULSE